开发环境

@M了个J

https://github.com/CoderMJLee http://cnblogs.com/mjios



码拉松





■ 开发工具

□eclipse (或者 IntelliJ IDEA)

✓ 明亮、简洁、舒服

- ✓ 多个项目可以在同一个窗口展示
- ✓ 上课过程中不会使用到后台开发的框架
- □支持Mac、Windows平台

□下载地址

<u>https://www.eclipse.org/downloads/</u>



■ JDK

□版本 ≥ 1.8

□下载地址

<u>https://www.oracle.com/technetwork/java/javase/downloads/index.html</u>

Managana 配置环境变量 (windows)

系统属性	;
计算机名 硬件 高级 系统保护 远程	
要进行大多数更改,你必须作为管理员登录。 性能 视觉效果,处理器计划,内存使用,以及虚拟内存	
	设置(S)
用户配置文件 与登录帐户相关的桌面设置	
	设置(<u>E</u>)
启动和故障恢复	
系统启动、系统故障和调试信息	
	设置(<u>T</u>)
	不境变量(<u>N</u>)
确定取消	í 应用(<u>A</u>)

境变量		
MJ Lee 的用户变量(<u>U</u>)		
变量	 ſ	
OneDrive	C:\Users\MJ Lee\OneDrive	
Path	D:\Program Files\Java\jdk1.8.0_20	1\bin;D:\Program Files\Java\jd
PATHEXT	.COM;.EXE;.BAT;.CMD;.VBS;.VBE;.JS	S;.JSE;.WSF;.WSH;.MSC;.RB;.RB
TEMP	E:\QQPCmgr\Temp	
ТМР	E:\QQPCmgr\Temp	
<u> </u>	新建(<u>N</u>)	编辑(<u>E</u>) 删除(<u>D</u>)
軍环境变量		×
D:\Program Files\Ja	va\jdk1.8.0_201\bin	
D:\Program Files\Ja	va\jdk1.8.0_201\jre\bin	
C:\Ruby24-x64\bin		编辑(E)
C:\Users\MJ Lee\Ap	pData\Local\Microsoft\WindowsApps	
C:\Users\MJ Lee\AppData\Roaming\npm		浏览(B)
C:\Users\MJ Lee\Ap	pData\Local\GitHubDesktop\bin	(A320(<u>0</u>)
%USERPROFILE%\AppData\Local\Microsoft\WindowsApps		
D:\Program Files\M		

D:\Program Files (x86)\Tesseract-OCR

2)



Mac

Ś	Eclipse	File	Edit	Source
	About E			
	Prefere	Ж,		
	Service			
	Hide Ec Hide Ot Show A	lipse hers II	∃第 ∃第プ	1
	Quit Ec	lipse	жc	2

Windows

JN	Window	Help		
7	New	Window	1	
	Edito	or	>	
	Арре	earance	>	
	Shov	v View	>	
	Pers	pective	>	
	Navi	gation	>	
	Prefe	erences		

	Desferreres	
	Preferences	
font 🛛 😵	Colors and Fonts	
General Appearance	Colors and Fonts (font, size, type, ? = any character, * = any string) :	
Colors and Fonts	type filter text	
Team	Active hyperlink text color	Edit
	Ag Banner Font	Lies System Fant
	Content Assist background color	Ose System Font
	Content Assist foreground color	Reset
	Counter color	
	Decoration color	
	$A\alpha$ Dialog Font	Edit Default
	Error text color	
	Aa Header Font	Go to Default
	Hyperlink text color	
	Information background color	Expand All
	Information text color	
	Match highlight background color	
	Qualifier information color	
	Range indicator color	
	AgText Editor Block Selection Font	
	Aa Text Font	
	▶ 🙀 Debug	
	Description:	
	The text font is used by text editors.	



■ 右击红色框区域,然后勾选: Show Line Numbers

🚺 Test.java 🕱	
1 package com.mj;	
3 public class Test { 4	
5 Dublic Static void ma • Toggle Breakpoint 企業B Disable Breakpoint 企Double Click	in(St
Go to Annotation	
Add Bookmark Add Task	P
✓ Show Quick Diff 个企Q	
 ✓ Show Line Numbers Folding 	
Preferences	
Breakpoint Properties %Double Click	J
	Test.java X 1 package com.mj; 2 3 3 public class Test { 4 5 5 public static void ma • Toggle Breakpoint Disable Breakpoint ☆ XB Disable Breakpoint ☆ Double Click Go to Annotation %1 ✓ Validate %1 Add Bookmark Add Task ✓ Show Quick Diff ^ûQ ✓ Show Line Numbers Folding Folding Preferences Breakpoint Properties %Double Click



- 代码提示
- ■Mac: Option + /
- □Windows: Alt + /
- 错误修复
- ■Mac: Command + 1 ■Windows: Ctrl + 1
- 快速生成代码
- Mac: Option + Command + S
- □Windows: Alt + Shift + S

■ 自动导入所需要的类 ■ Mac: Command + Shift + O ■ Windows: Ctrl + Shift + O





■ 将需要代码提示的字符输入到下面的文本框

口比如输入.ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789









😫 Existing Projects into Workspace

Projects from Folder or Archive

右键

	Copy QuaPasteDelete	alified Name		Select an import type filter text	wizard:
	Remove Build Path	rom Context	Ctrl+	✓ ➢ General	e File
	 Import Export Open Pro Assign W 	ject orking Sets		Existing File Sys Prefere Project Git	y Project tem inces is from F
Select ro Select <u>a</u> Projects:	oo <u>t</u> directory: rchive file: 复杂度 (F:\Seen	F:\Seemygo\恋上 hygo\恋上数据结构	数据结构与算法\03 > 5算法\03-代码\01-复	B <u>r</u> owse B <u>r</u> owse Select All Deselect All R <u>e</u> fresh	<

< <u>B</u> ack	<u>N</u> ext >	<u>F</u> inish	Cancel